

## 3-BUTTON HAND MIC DESIGN



Give you more control with one hand

## D.W. Dual Channel Watch

Enable you to use 2 channels at the same time.



## MY PILOT CB LEGEND II PLUS

Mobile CB Radio

## ASQ Automatic Squelch Control/SQL



Suppress undesirable background noises when not in communication. Squelch does not affect neither sound nor transmission power, but allows a considerable improvement in listening Comfort.

# LEGEND II PLUS

## Mobile CB Radio

### Key Features



**Dual Watch**  
Monitors 2 preselected Ch.  
simultaneously



**RF Gain Control**



**T.O.T. (Transmit  
time out timer)**



**LED Indicator**  
LED Indicating S-Meter,  
Power-Meter, Channel



**AM/FM Multi-bands  
(Selectable)**



**ASQ (Auto squelch  
control)/ SQL**



**Roger Beep  
(Selectable)**



**3.5mm Socket  
for External  
Loudspeaker**



**Emergency CH9/19**



**Hi-Cut Function**  
Eliminate High Frequency  
Interference



**Key Tone  
(Selectable)**

### Specifications

#### General

|                     |                              |
|---------------------|------------------------------|
| Channels            | 40                           |
| Modulation          | AM/FM                        |
| Frequency Range     | 26.965 - 27.405 MHz          |
| Frequency Tolerance | +/-200Hz                     |
| Input Voltage       | 13.2V DC                     |
| Dimensions          | 125(L) x 38(H) x 126.5(D) mm |
| Weight              | Approx. 0.6 kg               |
| Antenna Impedance   | 50Ω                          |

#### Receiver

|                                  |                        |
|----------------------------------|------------------------|
| Max. Sensitivity at 20dB Sinad   | <1μV                   |
| Frequency Image Rejection Rate   | >60dB                  |
| Adjacent Channel Selectivity     | >60dB                  |
| Intermediate Frequency Rej. Rate | >60dB                  |
| Drain                            | <700mA                 |
| Squelch Sensitivity              | Min. <0.5μV; Max. =1mV |
| Frequency Response               | 300Hz to 3KHz          |
| Maximum Audio Power              | >2W                    |

#### Transmitter

|                                   |                         |
|-----------------------------------|-------------------------|
| Maximum Output Power              | 4W                      |
| Transmission Interference         | <4nW                    |
| Audio Response                    | 300Hz to 3KHz           |
| Emitted Power in the Adj. Channel | <20μW                   |
| Microphone Sensitivity            | 7mW                     |
| Drain                             | <1.8A (with modulation) |
| Modulated Signal Distortion       | 3%                      |

All stated specifications are subjected to change without notice or obligation.



**M-Tech Dynamic Corporation Ltd**

Unit 1705, Grandtech Center, 8 On Ping Street,  
Shatin, New Territories, Hong Kong

[www.M-Tech.com.hk](http://www.M-Tech.com.hk)



#### Your Local Dealer

