



MAX-6

SPECIFICATIONS

- Meets the CE standard
- Built-in AC Adapter
- Input: 100-240V ~50/60Hz 2.5A
- Output: 6 x (7.2V DC 1A)
- Charging indicator: Red light
- Fully charged indicator: Green light
- Dimensions (W x H x D): 440 mm x 150 mm x 272 mm
- Weight: 2.69 kg

MAX-6 (I-01)

For ICOM IC-F11/21, IC-V82/U82, IC-V8

- BP-222N Ni-Cd battery
- BP-209N Ni-Cd battery
- BP-210N Ni-MH battery

MAX-6 (I-02)

For ICOM IC-F14/24, IC-F3020/4020 series

- BP-231 Li-ion battery (#)
- BP-232N Li-ion battery (#)

MAX-6 (I-03)

For ICOM IC-V80, IC-T70A

- BP-264 Ni-MH battery
- BP-265 Li-ion battery (#)

MAX-6 (K-02)

For KENWOOD TK-2202/3202, TK-2207/3207, TK-2217/3217

- KNB-29N Ni-MH battery
- KNB-30A Ni-Cd battery

MAX-6 (M-01)

For MOTOROLA GP328/338, GP340/380

- HNN9003 Ni-MH AA Bluetooth battery
- HNN9008 Ni-MH battery
- HNN9009 Ni-MH battery
- HNN9010 Ni-MH battery
- HNN9011 Ni-Cd battery
- HNN9012 Ni-Cd battery
- HNN9013 Li-ion battery (#)
- WPNN4045 Ni-MH battery
- PMNN4045 Ni-MH battery

MAX-6 (V-01)

For VERTEX VX-150/160/170/180, VX-410/420 series

- FNB-64 Ni-Cd battery
- FNB-V57 Ni-Cd battery
- FNB-83 Ni-MH battery
- FNB-V67 Li-ion battery (#)

(#): When Li-ion is used, optional charging tray is required.



Made in Hong Kong